


100C5 Froet Drain® Roof Drain Submittal

The Froet Drain® bi-functional roof drain has two independent systems with two inlets and two outlets. It is to be used in any flat roof construction. All drain parts are cast iron with the exclusion of the overflow riser pipe which is steel. Connections are all no hub.

Installation Tips:

The extensions are to be used to provide clearance of the primary outlet when used with thicker decks and/or thicker insulations. Froet Industries recommends that a sump be created with the insulation to promote flow and prevent ponding due to the height of the drain ring. Any ponding at the roof drain is likely to increase the frequency of the drain strainer becoming obstructed with debris. The roofing contractor needs to install roofing membrane so as to not obstruct the primary sump area



Standard roof drain supplied with 5 inch high primary strainer and 6 inch high overflow.

Low Profile roof drain supplied with 3 inch high primary strainer and 4 inch high overflow.

Project Options

LP	Low Profile	DEX-2	2" Extension
DC	Deck Clamp	DEX-4	4" Extension
OFS	Overflow strainer	DEX-6	6" Extension
DP	Drain Pan	IG	IRMA Guard
DMP	Deck Mounting Plate	CFW	Control Flow Weir
SP	Sumped Pan	VP	Vent Pipe
FR	Finishing Ring	ER-1.5	Elevation Ring for 1.5" Insul
		ER-2	Elevation Ring for 2" Insul



Please note: Overflow strainer not included with base drain. The OFS designation must be in part number to include overflow strainer

Project name: _____
 Contractor: _____
 Gen Cont: _____
 Design Firm: _____

Froet Industries LLC 1741 Industrial Drive
 Sterling Illinois 61081
 ph. 815.626.7922 fx. 815.626.0702
 www.froetindustries.com